










REF.	FA 40 902 20
CE	EN 358-1999
LG. (MIN. / MAX.)	1.2 m / 2.0 m
MAT.	● PA 11 mm Polyamide
	
MAT. 	
	0.69 KG

MAT. 	MAT. 
Matière	Matière connecteurs
Material	Material of connectors
Material	Material de los conectores
Materia	Materie connettori
Material	Material der Verbinder
	Matière boucle de réglage / coulisseau
	Material of adjustment buckle / rope grab
	Material de hebilla de ajuste / corredera
	Materia fibbia di regolazione / anticaduta scorrevole
	Material der Einstellschnalle/des Gleitelements

HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 36 cm / 25
AET N°2777/10351-02/E03-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D F114/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16030-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom