

Motorized workshop gantry

VGIM



I-profile

VERLINDE
LIFTING EQUIPMENT

1250 KG



Option :
hoist and
travelling trolley

Main isolator
in standard



Loads from
1,000 kg
to 6,300 kg

Motorized
floor motion
under load

► Technical characteristics

- > Motorized VERLINDE gantry crane for indoor and outdoor use.
- > Use on a smooth and clean floor.
- > Welded construction.
- > 2 motorized non swivel polyurethane wheels.
- > 2 castor polyurethane wheels.
- > Electrical equipment with mobile pendant (low voltage 48V).
- > 2 travelling speeds 10 m/min and 20 m/min with inverter.
- > Swiveling of the gantry by inversion of the motors.
- > 2 swiveling speeds.
- > Reversing switch on the pendant.
- > 4 safety full stops.
- > Protection: 3 layers.
- > RAL 1028 yellow polyurethane finish.
- > Maximum hoisting speed = 16 m/min.
- > Maximum traveling speed = 10 m/min.

► Options

- > Remote control
- > Reel 18 m P < 2 kW.
- > Reel 18 m P < 7 kW.
- > Batteries for independent gantry.



Gantries crane technical guide is available from our web site: VERLINDE.COM

► Load capacity

